Product data sheet


LUCAS X (1-ARMED) 9.850.2056.15 LEIPZIGER LEUCHTEN






Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

5 1	- I I-		
Nominal lamp power	100 W	LOR	84%
Lamp flux	10400 lm	Total flux	8713 lm
Luminous efficacy	76 lm/W	Total power	115 W
CCT	2000 K		
CRI	25		



1 x High pressure sodium vapour lamp

70 W	LOR	84%
5600 lm	Total flux	4691 lm
57 lm/W	Total power	83 W
2000 K		
25		
	5600 lm 57 lm/W 2000 K	5600 lm Total flux 57 lm/W Total power 2000 K

ower: 83-115 W
on labels: CE, F