



Product data sheet

1849 BITTA 3 LED - FLOOR 4000K CRI 80 27.4W CLD CORTEN
511443-2191
DISANO



Housing: in die-cast aluminium. Base: in die-cast aluminium. Diffuser: in polycarbonate, transparent, anti-glare, shatterproof and V2 self-extinguishing, UV stabilised. Coating: pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: - with air circulation valve. - equipped with plug-socket for quick installation Temperature Chart (Description): -20 °C ÷ +40 °C

Light output 1



1 x LED			
Nominal lamp power	27.4 W	LOR	100%
Lamp flux	2394 lm	ULOR	9%
Luminous efficacy	87 lm/W	Total flux	2394 lm
CCT	4000 K	Total power	27.4 W
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 14.61 in
Width: 17.24 in
Height: 94.25 in

Adjustability

Fixed

Design

Material impression: Aluminum

Electric

System power: 27.4 W
Appliance Class: II

Protection

IP: 66
IK: 08
Designation labels: CE