


Product data sheet

LINEAR LIGHTING
V1-R0-9X822-02000-4002340 X-LINE 0,75 M FOR CONTINUOUS LINES 23W 4000K
VARTON




IP
40

IK
01

• Extruded aluminum luminaire with flexible modular system for different shapes • L/T/X connectors • Continuous lines up to 30 m Application
• Retail spaces • Administrative facilities Installation • Surface-mounted • Suspended (optional) Input voltage (AC, 50Hz), V: 176...264 AC
frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: YXJ4 Color rendering index: 80-89 Protection class: I
Mounting method: Pendant Ingress protection (IP): IP40 Radiation angle: Radiation angle, °: 100 Impact resistance: IK01 Power factor: 0,95
https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/x-line-dlya-sborki-v-liniyu/x-line-0-75-m-dlya-sborki-v-liniyu/svetodiodnyy-svetilnik-var-ton-x-line-dlya-sborki-v-liniyu-23-vt-4000-k-750x63x100-mm-ra19005-chernyy_2/

Light output 1



1 x LED			
Nominal lamp power	23 W	LOR	100%
Lamp flux	2300 lm	Total flux	2300 lm
Luminous efficacy	100 lm/W	Total power	23 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 29.53 in
Width: 2.48 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 23 W

Protection

IP: 40
IK: 01