Product data sheet


LIGHTING FOR ADMINISTRATIVE AND OFFICE BUILDINGS
V1-R3-00350-30OPA-4006040 GR350/F 2.0 1219X325X50 MM IP40 60W 4000K OPAL EM 1H
VARTON



IP 40 IK 02

LED luminaire solution for GRILIATO ceilings with frame. Stainless steel housing with white powder coating. Application: administrative facilities For GRILIATO suspended ceilings with special rails. Can be fixed at the level of GRILIATO cells with a height of 30, 40 or 50 mm. Input voltage (AC, 50Hz): 176...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ4 Height/depth: 50 Length: 1 219 Protection class: I Ingress protection (IP): IP40 Impact resistance: IK02 Width: 294 Power factor: 0,95
https://www.varton.ru/products/ofisnoe-osveshchenie/varton-dlya-grilyato-gr-seriya-2-0/gr350-f-2-0-1219kh325kh50-mm-ip40/svetodiodnyy-svetilnik-varton-gr350-f-2-0-60-vt-4000-k-1219kh325kh50-mm-mont-1188kh294-mm-s-ramkoy-p_4/

Light output 1



1 x LED

Nominal lamp power	60 W	LOR	100%
Lamp flux	7680 lm	Total flux	7681 lm
Luminous efficacy	128 lm/W	Total power	60 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.99 in
Width: 11.57 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 60 W

Protection

IP: 40
IK: 02