Product data sheet


SIDELITE ROUND FERROMURANO
311909.004.76
RZB



IP 40 IK 02

Series: Sidelite Round FerroMurano Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Cover: painted aluminium. Frame: anodised aluminium. Diffuser: made by hand from green FerroMurano glass. Canopy: anodised aluminium, D 263mm, H 40mm. 3 point steel cable suspension, infinitely height adjustable. Integrated converter. Lateral light emission with LED. LED included. Available Colours: anodised aluminium Type of Installation: Pendant Dimensions: D 457, H 15 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 2500lm System power: 38W Beam Angle: 106° Number of fittings B10A: 12 Number of fittings B16A: 20 Inrush current: 30A Unified Glare Ratio: 21,1 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	38 W	CRI	80
Total flux	2500 lm	LOR	100%
Luminous efficacy	66 lm/W	Total power	38 W

Mounting mode

Pendant

Shape and measurements

Height: 0.59 in
Diameter: 17.99 in

Adjustability

Fixed

Electric

System power: 38 W

Protection

IP: 40
IK: 02