


Product data sheet

WALL 8.1 L [3000K 3.5W 230VAC]
PL8112405LC
L&L LUCE&LIGHT



Reading lamp; surface mounted (wall); Power: 2,5W, 3,5W; Power supply: 230Vac; Lumen output at source: 145 lm (3000K, 3.5W), 109 lm (3000K, 2.5W); Delivered lumen output: 78 lm (3000K, 25°, 2.5W), 103 lm (3000K, 25°, 3.5W); 1 power LED, 1/4 ANSI BIN, 50 000h L90 B10 (Ta 25°C); LED colour: 2700K, 3000K, 4000K, 5000K; Optics: 10°, 25°, 40°; Material: body in aluminium, plate in steel, arm in brass; Finishes: satin, chrome; built-in power supply unit; includes 0,30 m two-core cable; Ingress protection: IP20; chrome finish: white plate; satin finish: satin plate; Operating temperature: 0°C – +45°C; Photobiological safety: photobiological safety: risk group 1 according to EN 62471:2006; Appliance class: I; Weight: 370 g; Dimensions: Ø22x32 mm; Energy efficiency class: A / A+ / A++; Accessories: WC0301 Outer casing; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	3.5 W	CRI	80
Total flux	105 lm	LOR	100%
Luminous efficacy	30 lm/W	Total power	3.5 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.07 in

Width: 0.91 in

Height: 3.54 in

Adjustability

Free

Electric

System power: 3.5 W

Appliance Class: I

Protection

IP: 20