



Product data sheet

DELTA LED
507031
FLOS



• Wall light for outdoor installation on wall. • Configuration: turned aluminium body (EN AW 6060 alloy). 316L stainless steel fixing bracket. • Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Extra clear tempered glass with silkscreen border, fixed to the body by a double-sided tape.

Light output 1



1 x LED			
Nominal lamp power	3.6 W	LOR	99%
Lamp flux	215 lm	Total flux	212 lm
Luminous efficacy	47 lm/W	Total power	4.5 W
CCT	6000 K		
CRI	70		

Mounting mode

Wall mounted

Shape and measurements

Length: 1.97 in

Width: 3.94 in

Height: 1.97 in

Adjustability

Fixed

Electric

System power: 4.5 W

Appliance Class: III

Protection

IP: 65

IK: 05