
Product data sheet

R2L2 S 36L35 WR 740 CL2
96268469
THORN LIGHTING



A small size LED road lighting lantern with 36 LEDs driven at 350mA with Wide Road optic. Electronic, fixed output control gear. Class II electrical, IP66, IK08. Housing: die-cast aluminium, powder coated textured light grey. Diffuser: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. Complete with 4000K LED. For lateral mounting to Ø34/42mm spigots an adaptor (59005490 R2L2 MA34/42 NPA) should be ordered separately. Dimensions: 655 x 362 x 155 mm Total power: 40 W Weight: 9.32 kg Scx: 0.05 m²

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	40 W	CRI	70
Total flux	5641 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	40 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 25.79 in
Width: 14.25 in
Height: 6.10 in
Weight: 9.3 kg

Design

Material impression: Aluminum

Electric

System power: 40 W
Voltage: 230 V AC
Appliance Class: II

Protection

IP: 66
IK: 08
Designation labels: CE, ENEC