


# Product data sheet

MARVIK 4 WALL SURFACE LUMINAIRES  
MV-30031-N-W40  
LIGMAN




- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	11 W	CRI	80
Total flux	910 lm	LOR	100%
Luminous efficacy	83 lm/W	Total power	11 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	11 W	CRI	80
Total flux	910 lm	LOR	100%
Luminous efficacy	83 lm/W	Total power	11 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 7.87 in  
Diameter: 4.13 in  
Weight: 1.7 kg

## Adjustability

Fixed

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 22 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 08

Surface temperature: 40°C