

# Product data sheet


RICHARD BII (FLOWER BED FITTING)  
9.880.5307.05  
LEIPZIGER LEUCHTEN



IP  
55

Decorative luminaire for lanes, driveways, terraces, gardens, and for night illumination and hazardous areas. - Impact-resistant clear/opal polycarbonate cylinder, UV-stabilized - Mirror lamellae for Richard BII made of burnished, anodized highest-grade aluminium - Reflector made of impact-resistant RESIST plexiglass, inside finished in white paint, outside painted in colour - Unit carrier made of corrosion-resistant cast aluminium, painted - Upright tube made of special steel, painted - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



|                              |         |             |        |
|------------------------------|---------|-------------|--------|
| 1 x Compact fluorescent lamp |         |             |        |
| Nominal lamp power           | 18 W    | LOR         | 35%    |
| Lamp flux                    | 1200 lm | ULOR        | 11%    |
| Luminous efficacy            | 22 lm/W | Total flux  | 424 lm |
| CCT                          | 2899 K  | Total power | 19 W   |
| CRI                          | 90      |             |        |

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 11.42 in  
Diameter: 7.09 in

## Electric

System power: 19 W

## Protection

IP: 55