


Product data sheet

DKN CLASSIC
10143.002.1
RZB




IP
40

IK
02

Series: DKN-Classic, seidenglanz Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: metal, galvanised. Diffuser fastening: tilt springs (DKN system: push/tilt system). Diffuser: hand-blown opal glass, silk finish. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 400, H 125 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 1100lm System power: 13W Beam Angle: 121° Number of fittings B10A: 114 Number of fittings B16A: 182 Number of fittings C10A: 114 Number of fittings C16A: 182 Inrush current: 0,15A Unified Glare Ratio: 16,3 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13 W	CRI	80
Total flux	1100 lm	LOR	100%
Luminous efficacy	85 lm/W	ULOR	21%
		Total power	13 W

Mounting mode

Wall mounted

Electric

System power: 13 W

Shape and measurements

Height: 4.92 in
Diameter: 15.75 in

Protection

IP: 40
IK: 02

Adjustability

Fixed