

Product data sheet


LOUIS II (SINGLE ARM)
9.616.1032.07
LEIPZIGER LEUCHTEN



IP
55

recom. pole height: 4.00m – 6.00m light standards: low, medium and high lighting requirements lamp: excl. metal halide, sodium, compact fluorescent lamps; incl. CosmoPolis or incl. 1 glarefree U LED module 2 colour temperature: 2.800K, 3.000K warm white or 4.000K neutral white gear: HCI and NAV: incl. low loss ballast, ignitor and condensator; electronic ballast on request; CDO, CPO, compact fluorescent lamps: incl. electronic ballast; LED: electronic driver up to 100.000 hours; U LED: CLO mode LED life expectancy: up to 50.000 hours/ L100 or 100.000 hours/ L90 light control: at extra cost: dimming; power reduction; U LED: external change of dim settings subsequently or CLEVER LIGHT 10 optical system: louvre system for vertically mounted, coated lamps (except CPO) and directed light for wide spacings; R U LED: with extra inner laying satined anti-glare tube; U LED: vertically mounted module, diffuse light distribution: symmetrical, asymmetrical or asymmetrical with back shield luminaire head: with upper light, canopy and cap made of aluminium; with a special white, reflective underside finish; base made of corrosion-resistant cast aluminium; powder coated colour: RAL or DB glazing: PMMA RESIST, high-impact resistant; LOUIS II, II/ R-U LED: clear; LOUIS II U LED: satined wiring: completely wired; via a plug and socket connector below the luminaire head installation: 1 or 2 brackets for post top \varnothing 76mm accessory: lamp (except CPO, LED), cable, column, pole accessories – to be ordered separately application areas: residential and local distribution roads, schools, home for elderly people, hotels, factory premises, parkways, squares, car parks, shopping center, pedestrian zones

Light output 1



1 x Metal halide lamp

Nominal lamp power	70 W	LOR	50%
Lamp flux	7200 lm	ULOR	10%
Luminous efficacy	40 lm/W	Total flux	3591 lm
CCT	3000 K	Total power	89 W
CRI	90		

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.23 in
Diameter: 7.87 in

Adjustability

Height adjustable

Electric

System power: 89 W

Protection

IP: 55