


Product data sheet

X-WALL K9 LED 1300 PLX E IP44 24 840 / L-575MM
19.4355.2221.24
LUXIONA



Indoor luminaire. Assembly: mounted on wall. The body material is aluminum. Colour - anodised aluminum. Luminaire dimensions: 574 x 50 x 60 mm. Weight 1 kg. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 65,30%. Beam angle: asymmetric light distribution - $I_{max}=-47^{\circ}$. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B50 (2). Luminaire luminous flux: 927 lm. Power of luminaire: 9 W. Luminaire's light efficiency: 103 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cos ϕ : >0,9. Circuit load capacity: 23 (B10), 36 (B16), 35(C10), 60 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP44. Impact resistant: IK04. Protection against electric shock: I. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



1 x LED			
Nominal lamp power	9 W	LOR	83%
Lamp flux	1420 lm	Total flux	1185 lm
Luminous efficacy	158 lm/W	Total power	9 W
CCT	4000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 22.60 in
Width: 1.97 in
Height: 2.36 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 9 W
Appliance Class: I

Protection

IP: 44
IK: 04

Other operating numbers

Ambient temperature range: 41...86°F