
Product data sheet


HALO SURFACE WHITE 1220MM
R48A122-9016C1930L3S
PLANLICHT



IP 20


LED LO 3000K CRI>90 40,3W 4204lm DALI https://katalog.planlicht.com/en-gb/fam-halo/

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.04 W	CRI	90
Total flux	526 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	5.04 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.04 W	CRI	90
Total flux	526 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	5.04 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.04 W	CRI	90
Total flux	526 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	5.04 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.04 W	CRI	90
Total flux	526 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	5.04 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.04 W	CRI	90
Total flux	526 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	5.04 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	5.04 W	CRI	90
Total flux	526 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	5.04 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	5.04 W	CRI	90
Total flux	526 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	5.04 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	5.04 W	CRI	90
Total flux	526 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	5.04 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 48.03 in
Width: 48.03 in
Height: 2.52 in

Adjustability

Fixed

Electric

System power: 40.3 W

Protection

IP: 20
Designation labels: CE