



Product data sheet

MINI MULTIPLE TRIMLESS FOR SMART KUP LED 4000K FLOOD GE WHITE STRUC
12535209+12556109
MODULAR




Highly versatile Twenty years after its initial launch, Mini multiple is still a coveted luminaire. Mini multiple is the reference of our architectural lighting portfolio. The technology is on full display and allows this luminaire to fit well into both a minimalist and an industrial-chic environment. The gimbaled system allows you to direct the light source at any angle of your choice. Mini multiple has a very subtle alu trim. Available in one-, two-, three- and four lamps versions in different colours. Connect Mini multiple with Smart by adding the Smart frontrings to your recessed spot.

Light output 1



1 x LED			
Nominal lamp power	6.2 W	LOR	92%
Lamp flux	590 lm	Total flux	541 lm
Luminous efficacy	87 lm/W	Total power	6.2 W
CCT	4000 K		
CRI	90		



1 x LED			
Nominal lamp power	9.2 W	LOR	92%
Lamp flux	792 lm	Total flux	727 lm
Luminous efficacy	79 lm/W	Total power	9.2 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed, Wall recessed

Shape and measurements

Length: 4.72 in
Width: 4.72 in
Height: 4.72 in
Weight: 0.69 kg

Adjustability

Free

Electric

System power: 6.2-9.2 W
Appliance Class: III

Protection

IP: 20
IK: 01