

Product data sheet

JUNISTAR ECO ISOSAFE BLACK 590LM 3000K RA 98 TRAILING EDGE DIMMING


7021989052241

SG ARMATUREN



Junistar Eco IsoSafe is a cost-efficient downlight for indoor use with a 42° beam angle and 30° tilt function. A flexible diameter of Ø68-83mm makes Junistar Eco a great choice for refurbishing older ceilings. Junistar Eco IsoSafe is tested to be 100% airtight against plaster board ceilings. Supplied as an 8-pack incl drivers. Our IsoSafe products can be mounted directly in insulation (IsoSafe). Supplied as an 8-pack. IP44 protection rating Light distribution Direct Light technic LED (not exchangeable) 7W 3000K Ra 98 SDCM 2 L90/B10 >100,000 hrs Control/Dimming Trailing edge dimming Protection Class II SELV IP44 Materials and finish Housing: Aluminium Colour: Black (RAL 9004) Optics: Tempered glass Mounting/Connection Recessed, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 105, B16: 168, C10: 105, C16: 168

Light output 1



1 x LED

Nominal lamp power

7 W

LOR

100%

Lamp flux

590 lm

Total flux

590 lm

Luminous efficacy

84 lm/W

Total power

7 W

CCT

3000 K

CRI

98

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.54 in

Width: 3.54 in

Height: 1.99 in

Adjustability

Tiltable

Design

Color of housing: Black

Electric

System power: 7 W

Appliance Class: III

Protection

IP: 44