
Product data sheet

TKGC L63 60° LE3
TANEK CORNICE GLASS EMERGENCY
DEXTRA




Tanek Glass Cornice - 1500mm, IP65, IK10 Cornice mounted luminaire, constructed from robust 1.2mm CR4 steel, toughened glass diffuser, weather resistant and salt spray tested, tamper resistant diffuser fixings, two 20mm side cable entries. Options: LE3 - Lithium Emergency LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* R25E - Reacta 25, On / Off High Frequency R25C - Reacta 25, Corridor Mode* RLM - Reacta-Link Wireless Microwave Presence & Bright Out RCME - Reacta-Control Wireless Microwave On/Off RCMC - Reacta-Control Wireless Microwave Corridor Mode* *Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off. WH - White Finish BL - Black Finish C83 - CRI 80, 3000K

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	39.7 W	CRI	80
Total flux	4483 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	4%
		Total power	39.7 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	367 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	4%
		Total power	3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.62 in
Width: 7.87 in
Height: 4.72 in

Electric

System power: 42.7 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Adjustability

Fixed

Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Single battery 3 h

Emergency sign: N/A

Protection

IP: 65

IK: 10

Resistant to impact of balls

Designation labels: CE