

Product data sheet

INDIGO COMBO BETA OPTI 300X1200 840 VTB HL CLO
24197-529
FAGERHULT



Installation Recessed mounting in suspended ceilings. Unventilated or ventilated ceilings. Two optional designs: – for suspended ceilings with visible T-bars (15 or 24 mm). HB –for suspended ceilings with concealed T-bars and symmetrical ceiling tiles (thickness 20-22 mm). Four suspension fittings included. For fixed roofs (plaster etc.) suspension fittings for an HB body can be ordered separately. Connection Connected to 2.5 mm² 3-way terminal block 3 x 1.5 mm² (x2), with the possibility of through-wiring. 5 x 1.5 mm² (x2) when dimming. Can also be supplied with mains cable and earthed plug or chassis mounted snap-in connector. The luminaire housing and driver are connected via a Quick Connection System. Design Luminaire body of white enamelled sheet steel (RAL 9016). Louvre Beta Opti – double parabolic side and cross reflectors in semi-gloss metallized aluminium with excellent reflective properties (> 92%), assembled into one unit. An integrated opal acrylic diffuser film (PMMA) minimises the risk of uncomfortable glare from the diodes. Dimming e-Sense Organic – PIR sensor with presence and daylight control. All luminaires have master/slave functionality with IR communications. Miscellaneous Enclosure class IP 40 under suspended ceilings and IP 20 above suspended ceilings. Class III applies to the luminaire body only. The supplied driver is Class II but should be connected to a functional Earth.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	33 W	CRI	80
Total flux	4089 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	33 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.09 in
Width: 11.65 in
Height: 4.02 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 33 W
Appliance Class: II

Protection

IP: 40