



# Product data sheet

CEILING MOUNTED LUMINAIRE CHANNEL S OFFICE 24.5W 2150LM CRI  
2005.2664 - CHAN-SO CM1550 LED2150-830 RUN+ DALI E3H  
REGENT



Ceiling mounted luminaire Channel S Office with LED, system power: 24.5 W, standby power 0.5 W, luminous flux of luminaire 2150 lm, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19;  $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$ ), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, support profile in aluminium natural-colour anodised without ceiling trim, diffuser in polycarbonate (PC) satin, RUN+, rollable and office-suitable, for a perfectly glare-free light line with no visible interruptions, 1 integral control gear, DALI, with halogen-free wiring, 6-pole, with emergency unit, for non-maintained and maintained mode, with self-test, complete with battery pack, (burning life 3h), protection class I, ingress protection IP20, glow wire test 650 °C, impact strength: IK 08, for ambient temperatures -5 to +30 °C, this product contains a light source of energy efficiency class B L = 1550 mm, B = 65 mm, H = 61 mm,

## Light output 1



1 x LED

Nominal lamp power	47 W	LOR	100%
Lamp flux	2150 lm	Total flux	2150 lm
Luminous efficacy	46 lm/W	Total power	24.5 W
CCT	3000 K		
CRI	80		

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 61.02 in

Width: 2.56 in

Height: 2.44 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 24.5 W

Appliance Class: I

## Protection

IP: 20

IK: 08