
Product data sheet

3468 DENIA PRO 2 - PS FS3 4000K CRI 70 75W CLD GREY9007
340090-0054-0200-PS
DISANO



Housing: in die-cast aluminium and designed with a very small surface exposed to wind. Self-cleaning design with a smooth and slightly convex surface, specifically designed to reduce the adhesion of dust and residues. Attachment: 46/76mm in die-cast aluminium with clamps for fastening the fixture at different angles. Adjustable from -20° to 10° for side-mount applications; and from 0° to 20° for top-mount applications. Diffuser: extra-clear, tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI-EN 12150-1:2001). Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Special coating: Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. Heat Sink: integrated Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Laboratory tests: compliant with third-party certified vibration tests pursuant to ANSI C136.31: Street Lighting - Luminaire Vibration. Test level: 3.0G Level 2 for bridge/overpass applications.

Light output 1



1 x LED

Nominal lamp power	75 W	LOR	100%
Lamp flux	12150 lm	Total flux	12149 lm
Luminous efficacy	162 lm/W	Total power	75 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.85 in
Width: 10.28 in
Height: 3.58 in

Adjustability

Fixed

Electric

System power: 75 W
Appliance Class: II

Protection

IP: 66
IK: 09
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -22...122°F