


Product data sheet

L402/4348-6100-152-1110-11-8650
272002
STAHL



Linear luminaire With LED GRP industrial design Industrial design Type: L402/4348-6100-152-1110-11 Enclosure material: Polyester resin Translucent cover material: Polycarbonate Version: Standard Number of lamps: 1 Lamp wattage: 42 W Light distribution: 120°x120° with diffusing glass Colour temperature: 6.500 K Dimensions (L x W x H): 1.310 x 184 x 125 mm AC rated operational voltage: 220,00 - 240,00 V DC rated operational voltage: 200,00 - 250,00 V Min. ambient temperature: -40 °C Max. ambient temperature: +55 °C Note: Through wiring: Max. 3x16 A Max. ambient temperature 2: +60 °C Note: Through wiring 2: Max. 3x10 A Diffuser: With diffuser Through wiring: With 5 conductors 2.5 mm2 Ballast: VG Luxtronic 80 W 300 mA Threaded plate: 2x plastic Drilled holes: 3 x M25 Accessories: Provided Screw connections: 2 x M25 Ø 7 – 17 mm Cable entry material: Polyamide, black Stopping plug: 2 x M25 x 1.5 Stopping plug material: Polyamide, black For further information, see: r-stahl.com WebCode L402A

Light output 1 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	42 W	CRI	81
Total flux	5810 lm	LOR	100%
Luminous efficacy	138 lm/W	ULOR	2%
		Total power	42 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 51.57 in
Width: 6.61 in
Height: 5.07 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: Anthracite / graphite

Electric

System power: 42 W
Voltage: 240 V AC, 250 V DC, 230 V DC, 220 V DC, 220 V AC, 240 V DC, 230 V AC
Ballast: ECG
Appliance Class: I

Protection

IP: 66
IK: 10

Other operating numbers

Ambient temperature range: -40...140°F