



Product data sheet

MULTIDIR EVO SMALL DOUBLE RECESSED TRIMLESS
AU14-11V9F1XB60
LEDSC4




LedsC4 Multidir Evo Small Double Recessed Trimless AU14-11V9F1XB60V1 Downlight for indoor use. Adjustable light source. Structure material: Aluminium. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Transparent. Warranty: 5 Years. Product net weight (Kg): 2.23 Product length (mm): 200 Product width or diameter (mm): 100 Product height (mm): 88 Ø of the hole for recessing (mm): 200x100 Permitted ceiling thickness: 0-20 Class 2. IP: IP54. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Driver brand: TCI. Maximum power of light source: 25.1W. Colour temperature: 2700K. Colour rendering index: 92. MacAdam Steps: 2. Hours of life: 50.000h L80B20. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 2826. Real lm/W: 99. Voltage / frequency range: 220-240/50-60Hz. Voltage: 33.7. Equipment included: Yes. Total power: 28.5. Power factor: NULL. Dimmable equipment included: CASAMBI.

Light output 1



1 x LED			
Nominal lamp power	13.2 W	LOR	100%
Lamp flux	1413 lm	Total flux	1413 lm
Luminous efficacy	107 lm/W	Total power	13.2 W
CCT	2700 K		
CRI	90		

Light output 2



1 x LED			
Nominal lamp power	13.2 W	LOR	100%
Lamp flux	1413 lm	Total flux	1413 lm
Luminous efficacy	107 lm/W	Total power	13.2 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.87 in

Width: 3.94 in

Height: 0.12 in

Electric

System power: 26.4 W

Appliance Class: II

Protection

IP: 54

Adjustability

Fixed