


# Product data sheet

TUBS MODULAR VERTICAL RECTANGULAR 600X1500MM  
00-8271-05-M1  
LEDSC4




LedsC4 Tubs Modular Vertical Rectangular 600x1500mm 00-8271-05-M1 Pendant for indoor use. For downlighting. The optical module can easily be rotated 360°. Structure material: Aluminium. Structure finish: Black. Diffuser material: Methacrylate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 3.86 Product length (mm): 1619 Product width or diameter (mm): 729 Product height (mm): 400-2500 Ø of the hole for recessing (mm): 314x84 Permitted ceiling thickness: 10-50 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEAN WELL.. Maximum power of light source: 107.2W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG0. Real flux (lm): 3936. Real lm/W: 34. Voltage / frequency range: 100-305/50-60Hz. Voltage: 3. Equipment included: Yes. Total power: 115.3. Power factor: 0.95. Dimmable equipment included: DALI.

## Light output 1




1 x LED			
Nominal lamp power	40 W	LOR	100%
Lamp flux	1406 lm	Total flux	1406 lm
Luminous efficacy	35 lm/W	Total power	40 W
CCT	3000 K		
CRI	90		

## Light output 2




1 x LED			
Nominal lamp power	40 W	LOR	100%
Lamp flux	1406 lm	Total flux	1406 lm
Luminous efficacy	35 lm/W	Total power	40 W
CCT	3000 K		
CRI	90		

Light output 3



1 x LED			
Nominal lamp power	16.5 W	LOR	100%
Lamp flux	562 lm	Total flux	562 lm
Luminous efficacy	34 lm/W	Total power	16.5 W
CCT	3000 K		
CRI	90		

Light output 4



1 x LED			
Nominal lamp power	16.5 W	LOR	100%
Lamp flux	562 lm	Total flux	562 lm
Luminous efficacy	34 lm/W	Total power	16.5 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 40.31 in  
Width: 63.70 in  
Height: 0.63 in

Adjustability

Fixed

Electric

System power: 113 W  
Appliance Class: I

Protection

IP: 20