


Product data sheet

LOUI 50
925347.003.1
RZB




IP
20

IK
03

Series: LESS IS MORE 50;system Eckmodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Alea Optik System: Reflektorstruktur (ABS, Aluminium bedampft, hochglänzend) mit Diffusor aus vergilbungsfreiem Kunststoff (PMMA) opal für blendfreies Licht am Arbeitsplatz (UGR <19, Bildschirmgerecht gemäß DIN EN 12464-1). Nur optional: Lichtbandsystem vorbereitet für Seilabhngung! Colour: deep black, matt (RAL;9005) Length: 613;mm Width: 613;mm Height: 75;mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 28;W Rated luminous flux: 3550;lm Luminous efficiency: 127;lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP;20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	28 W	CRI	80
Total flux	3550 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	28 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.13 in
Width: 24.13 in
Height: 2.95 in

Adjustability

Fixed

Electric

System power: 28 W

Protection

IP: 20
IK: 03