


Product data sheet

VRT3 L200 HR E3
VERTECO3 EMERGENCY
DEXTRA




Verteco 3 - IP20 Industrial Luminaire with high rack optics. Steel body white powder coated paint finish and green polycarbonate end caps. Mounting to lighting trunking using standard 20mm brass bush and locknut assembly. Side entry panel mount with female power feed plug supplied. Options: E3 - Emergency control gear (1044 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest R18H - Reacta 18, Daylight and Presence Detection Sensor, Narrow Lens R18W - Reacta 18, Daylight and Presence Detection Sensor, Wide Lens R18HRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Narrow Lens R18WRF - Reacta 18, Daylight and Presence Detection Sensor, Wireless Version, Wide Lens

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.05 W	CRI	80
Total flux	1044 lm	LOR	100%
Luminous efficacy	258 lm/W	Total power	4.05 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	122 W	CRI	80
Total flux	18799 lm	LOR	100%
Luminous efficacy	154 lm/W	Total power	122 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 39.37 in
Width: 8.46 in
Height: 3.31 in

Electric

System power: 126.05 W
Ballast: ECG
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 20

Designation labels: CE