Product data sheet

SRT-SYSTEM IP64-SRGSCTB PP/1500 LED - GERÄTETRÄGER FIX CENTRAL.LINE.OPTIC | DEVICE MOUNT FIX CENTRAL.LI.. 14000 840 IP64 DALI2 VW RAL 9016 (SRT+19532006060)


REGIOLUX



IP 64 IK 03 CE

SRT-Quick-fit mounting system, IP 64 device mount, Modullänge/1500. Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Housing colour traffic white RAL 9016. Performance level: Powerful Performance (PP) - Powerful, universal all-rounder, sets very high standards for efficiency, service life and warranty period, Light distribution direct narrow/wide distribution by means of Central.Line.Optic of PMMA plastic, The lens optics ensure ease of installation and are easy to maintain thanks to the easy-to-clean surface. The density of the single-row lens arrangement ensures that the points merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 1535mm x 55mm x 37mm Beam angle: 80°(C0)/80° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 75000h L80/B10 (Tq 30°C), 100000h L80/B50 (Tq 30°C) Nominal luminous flux: 14382lm Luminaire luminous efficiency: 164lm/W Control gear: Electronic driver DALI2 (1 pcs.) System output: 88W Energy efficiency class/light source: B Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 30°C) Ambient temperatur: ta -20°C to 30°C Special properties: Ready for IoT UGR lat./long.: max. 22.3 / 21.4 Certification mark: IP64, Protection class I, ENEC10 VDE, F, D, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 7 years Regiolux GmbH Type: SRGSCTB PP /1500 LED 14000 840 DALI2 vw RAL 9016 Article number: 19532006060 Product deep link: https://www.regiolux.de/en/article/19532006060 General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	87.8 W	CRI	80
Total flux	14382 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	87.8 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 60.43 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 87.8 W
Appliance Class: 0

Protection

IP: 64
IK: 03
Designation labels: CE, ENEC

Design

Color of housing: White