Product data sheet

PRO-STRADA BASIC MICRO 35W
4031202X
PROLUMIA



IP 66 IK 08 CE

Color rendering: Ra >70 Operating temperature: -30°C - +50°C Rated life hours: > 100.000 (L80B10) LED driver (included): Inventronics Input: 200 - 240V AC 50-60Hz Power factor: > 0,95 Cable length: 0,6m, incl. male IP65 connector Input: 220-240V AC 50/60Hz Power factor: > 0,95

Light output 1



1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	4900 lm	ULOR	9%
Luminous efficacy	140 lm/W	Total flux	4900 lm
CCT	4000 K	Total power	35 W
CRI	80		



1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	4550 lm	ULOR	9%
Luminous efficacy	130 lm/W	Total flux	4550 lm
CCT	3000 K	Total power	35 W
CRI	80		



1 x LED

Nominal lamp power	35 W	LOR	100%
Lamp flux	4900 lm	ULOR	9%
Luminous efficacy	140 lm/W	Total flux	4900 lm
CCT	3000 K	Total power	35 W
CRI	80		

Mounting mode

Ceiling mounted, Pole top mounted

Electric

System power: 35 W
Appliance Class: 0

Shape and measurements

Length: 16.81 in

Width: 9.02 in

Height: 4.49 in

Protection

IP: 66

IK: 08

Designation labels: CE, ENEC