

# Product data sheet

RICHARD II (2-ARMED)  
9.893.3162.00  
LEIPZIGER LEUCHTEN



Mounting height approx. 3,00 - 4,50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge -Order pole, dia. 60 mm, separately Order pole for double-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	21 lm/W
CCT	3400 K
CRI	54

LOR	43%
ULOR	8%
Total flux	2922 lm
Total power	137 W




### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	19 lm/W
CCT	3400 K
CRI	54

LOR	43%
ULOR	8%
Total flux	1719 lm
Total power	89 W


## Light output 2



### 1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	21 lm/W
CCT	3400 K
CRI	54

LOR	43%
ULOR	8%
Total flux	2922 lm
Total power	137 W



**1 x High pressure mercury vapour lamp**

Nominal lamp power	80 W	LOR	43%
Lamp flux	4000 lm	ULOR	8%
Luminous efficacy	19 lm/W	Total flux	1719 lm
CCT	3400 K	Total power	89 W
CRI	54		

**Mounting mode**

Pole top mounted, Ceiling mounted

**Shape and measurements**

Height: 24.21 in

Diameter: 9.84 in

**Design**

Material impression: Matt

**Electric**

System power: 178-274 W

Ballast: ECG

Controller: DALI

**Protection**

IP: 55

Designation labels: CE, ENEC

**Other operating numbers**

Ambient temperature range: -4...95°F