

# Product data sheet


LENSES-EQ0597DAWS830B0350  
0837713  
RIDI



IP  
20

Recessed LED luminaire Design: Recessed LED single luminaire. Rigid luminaire housing in white powder-coated steel (similar to RAL 9016) with square 4-row lens arrays for high-efficiency light yield. Diffuser held in the luminaire housing with spring catches, hinges down on both sides. LED modules formed as a flat board. Mid-power LEDs for even illumination and maximum efficiency. LED driver prefitted in luminaire housing. Colour rendering in index Ra  $\geq$  80, colour temperature 3000 Kelvin (830). Electronic converter for LED, 220-240 Volt, 0/50-60 Hz and internal connector block. Suitable for direct voltage operation and use in central battery systems, 220-240 VDC. Mounting: Installation using suitable fixing kit (accessory) in sawn ceilings.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	21 W	CRI	80
Total flux	3500 lm	LOR	100%
Luminous efficacy	167 lm/W	Total power	21 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.50 in  
Width: 23.50 in  
Height: 2.36 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 21 W

## Protection

IP: 20