
Product data sheet


IQ SURF L LED4250-830 HFIX ASY
96629837
THORN LIGHTING



IP 40 IK 05

A lightweight, surface mounted, LED luminaire with MV Tech asymmetrical optic. Electronic, DALI dimmable control gear. Class I electrical, IP40, IK05. Body, diffuser, frame and endcaps: polycarbonate (Tpa) finished in white (close to RAL9016). Gear tray: pre-coated white steel. Complete with 3000K LED Dimensions: 1440 x 210 x 70 mm Total power: 40 W Luminaire luminous flux: 4000 lm Luminaire efficacy: 100 lm/W weight: 5.1 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	40 W	CRI	80
Total flux	4000 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	6%
		Total power	40 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 56.69 in
Width: 8.27 in
Height: 2.76 in
Weight: 5.1 kg

Design

Material impression: Plastic
Color of housing: White

Electric

System power: 40 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 05
Designation labels: CE