Product data sheet

DEFINE LED SUSPENDED LUMINAIRE S122DIP-S865D925U927-4F0-1E-UDD-D4

COOPER LIGHTING








Surface mount slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K and 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx, Lumawatt Pro and stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

Light output 1 (integrated)



| Lamp type | LED | CCT | 2700 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 60.5 W | CRI | 90 |
| Total flux | 5632 lm | LOR | 100% |
| Luminous efficacy | 93 lm/W | ULOR | 56% |
| | | Total power | 60.5 W |

Mounting mode

Pendant

Shape and measurements

Length: 48.00 in Width: 2.00 in Height: 1.00 in

Adjustability

Fixed

Electric

System power: 60.5 W

Protection

IP: 47