
Product data sheet


SINUS RECESSED FRAME BLACK PRISM. 1190MM
R33E119-9005E1840L3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40


low output LED 4000K CRI 90 42,8W 5431lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 26,3% https://katalog.planlicht.com/en-gb/fam-sinus/

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	679 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	5.35 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	679 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	5.35 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	679 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	5.35 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	679 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	5.35 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	679 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	5.35 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	679 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	5.35 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	679 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	5.35 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.35 W	CRI	90
Total flux	679 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	5.35 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 46.85 in
Width: 46.85 in
Height: 3.23 in

Adjustability

Fixed

Electric

System power: 42.8 W

Protection

IP: 40