## Product data sheet

FIT 35 48V DOUBLE DIM DALI 38° 3000K GW A3451231GW


ARKOSLIGHT



Fit 48V, is a spotlight for low voltage tracklight applications which is available in five sizes (50, 35, 35 double, 20 and 20 double). Cylindrical geometry and essential forms, it stands out for its minimalistic looking and its functionality as it can be orientated in any direction. The black perimeter around its mouth and its honeycomb accessory, highlights its anti-glare vocation.


IP 20

Light output 1



1 x LED			
Nominal lamp power	5.5 W	LOR	80%
Lamp flux	630 lm	Total flux	504 lm
Luminous efficacy	115 lm/W	Total power	5.5 W
CCT	3000 K		
CRI	90		

Light output 2



## 1 x LED

IXLLD			
Nominal lamp power	5.5 W	LOR	80%
Lamp flux	630 lm	Total flux	504 lm
Luminous efficacy	115 lm/W	Total power	5.5 W
CCT	3000 K		
CRI	90		

Mounting mode	Electric
Ceiling mounted, Contact rail, Wall recessed	System power: 11 W
Shape and measurements	Protection
Length: 1.38 in	IP: 20
Width: 1.38 in	
Height: 3.74 in	

## Created by luminaires.dialux.com (27 Apr, 2025)

Adjustability Rotatable, Tiltable