

# Product data sheet

PURA S ECO  
741904.004.1  
RZB




IP  
20

IK  
03

Series: Pura S ECO Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium, rotates 356° horizontally and swivels 180° vertically, heat resistant plastic ring. Reflector: faceted aluminium, passive cooling, open version. With multi adapter for 230V 3 circuit tracks. LED included. Available Colours: silver, metallic Type of Installation: Track on ceiling Dimensions: L 258, B 93, H 249 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 3150lm System power: 33W Beam Angle: 36° Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 16A Unified Glare Ratio: 18,6 EEC: A++

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	33 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	95 lm/W	Total power	33 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 3.66 in

Width: 10.16 in

Height: 9.72 in

## Adjustability

Rotatable, Tilttable

## Electric

System power: 33 W

## Protection

IP: 20

IK: 03