Product data sheet

AGALINE LED 20000 E 34 840 / L-2805MM
19.4213.5121.34
LUXIONA



IP 20 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is steel sheet. Colour - RAL 9016 (white). Dimensions: 2805 x 56 x 45 mm. Diffuser: none. Beam angle: (C0-C180) / (C90-C270) - 114,4° / 114,4°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 21745 lm. Power of luminaire: 115,4 W. Luminaire's light efficiency: 188,4 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 4 (B10), 7 (B16), 7 (C10), 12 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP20. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. Lenght 2805 mm avaliable only for special request.

Light output 1



5 x LED

Nominal lamp power	28.6 W	LOR	52%
Lamp flux	4165 lm	Total flux	10920 lm
Luminous efficacy	146 lm/W	Total power	143 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 110.43 in
Width: 2.20 in
Height: 1.77 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 143 W
Appliance Class: I

Protection

IP: 20
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F