Product data sheet


3401/3402 TRIANO LED HIGH-BAY FLOODLIGHT
3401 L120TB G2 D (34010 0141)
SCHUCH



IP 65 IK 09

LED high-bay floodlight, TRIANO, 84 W, 13500 lm, 161 lm/W, Class I, IP65, narrow wide beam, 5000 K, CRI≥ 80, Ta -25 °C/+55 °C, L80>100000 h (@Ta 25°C), L80>80000 h (@ Ta max), Optics PC clear, Closure Stainless steel (1.4301), Housing Die-cast aluminium, Colour grey, DB702N, for rooms with increased risk of fire, for food areas. LED high bay light fitting TRIANO. Die-cast aluminium housing, powder-coated, multi-part, thermally separated. ECG housing with incorporated ECG, eyebolt for 1-point mounting and connection plug. LED housing, three-part, with integrated cooling fin structure, LED modules as well as PC covers with integrated optics. LED modules, Multi-Layer Technology, with direct connection to the housing for perfect thermal management. ECG with overload and short circuit protection. Electrical connection by connection plug (FastConnect), male connector pre-installed, female attached. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting)., Width/Diameter 400,00 mm, Height 186,00 mm, Net weight 6,10 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	84 W	CRI	80
Total flux	13498 lm	LOR	100%
Luminous efficacy	161 lm/W	ULOR	7%
		Total power	84 W

Mounting mode

Pendant

Shape and measurements

Height: 7.32 in
Diameter: 15.75 in

Adjustability

Fixed

Electric

System power: 84 W
Appliance Class: I

Protection

IP: 65
IK: 09
Designation labels: CE