Product data sheet

DOWNTOWN NO TRIM Ø215 03.0455/TC-TEL/18W


FLOS






Luminaires for embedded installation indoor with fluorescent lamps and of halogenuro metalist. Optical body made in injected aluminium with powder-coated paint finish. Heatsink made in injected aluminium under pressure attached to the body of the luminaire. Lower and upper reflectors available made of anodized aluminium with specular finish. Fixed upper reflector. Inferior reflector formed by self reflector and a spreading lens of 4mm thick and a polycarbonate ring that fixes the reflector to the aluminium ring of the product. Available in two diameters 160mm and 215mm.

Light output 1



1 x Compact fluorescent lamp	
Nominal lamp power	

Nominal lamp power	18 W	Socket	Gx24Q-2
Lamp flux	1200 lm	LOR	49%
Luminous efficacy	33 lm/W	Total flux	591 lm
CCT	4000 K	Total power	18 W
CRI	80		



1 x Compact fluorescent lamp	

Nominal lamp power	18 W	Socket	Gx24Q-2
Lamp flux	1200 lm	LOR	49%
Luminous efficacy	33 lm/W	Total flux	591 lm
CCT	3000 K	Total power	18 W
CRI	84		

Mounting mode	Electric
Ceiling recessed	System power: 18 W
Shape and measurements	Protection
Height: 7.36 in	IP: 23
Diameter: 7.99 in	

Adjustability

Fixed