
Product data sheet


DEECOS P MICRO
911489.004
RZB



IP 20 IK 06


Series: DEECOS P micro Cylindrical pendant luminaire. Housing made of die-cast aluminium, powder-coated. Canopy made of powder-coated sheet steel, with magnetic attachment. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Black plastic ring and recessed LED to prevent glare from the side. Best colour rendering index Ra>90. Transparent suspension cable 3 m, can be shortened. High quality converter without flickering and stroboscopic effect. Colour: silver Diameter: 60 mm Height: 190 mm Suspension length: 3000 mm Lamp: LED Socket: without socket Colour temperature: 2700K Colour rendering index (CRI): 92 System power: 16 W Rated luminous flux: 1600 lm Beam angle Down: 38° Luminous efficiency: 100 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1




1 x LED

Nominal lamp power	16 W	LOR	67%
Lamp flux	1500 lm	ULOR	14%
Luminous efficacy	63 lm/W	Total flux	1001 lm
CCT	2700 K	Total power	16 W
CRI	92		




1 x LED

Nominal lamp power	16 W	LOR	67%
Lamp flux	1500 lm	ULOR	14%
Luminous efficacy	63 lm/W	Total flux	1001 lm
CCT	2700 K	Total power	16 W
CRI	92		




1 x LED

Nominal lamp power	16 W	LOR	67%
Lamp flux	1500 lm	ULOR	14%
Luminous efficacy	63 lm/W	Total flux	1001 lm
CCT	2700 K	Total power	16 W
CRI	92		




1 x LED

Nominal lamp power	16 W	LOR	67%
Lamp flux	1500 lm	ULOR	14%
Luminous efficacy	63 lm/W	Total flux	1001 lm
CCT	2700 K	Total power	16 W
CRI	92		



1 x LED

Nominal lamp power	16 W	LOR	67%
Lamp flux	1600 lm	ULOR	14%
Luminous efficacy	67 lm/W	Total flux	1067 lm
CCT	2700 K	Total power	16 W
CRI	92		



1 x LED

Nominal lamp power	16 W	LOR	67%
Lamp flux	1500 lm	ULOR	14%
Luminous efficacy	63 lm/W	Total flux	1001 lm
CCT	2700 K	Total power	16 W
CRI	92		

Mounting mode

Pendant

Shape and measurements

Height: 7.48 in

Diameter: 2.36 in

Adjustability

Fixed

Electric

System power: 16 W

Protection

IP: 20

IK: 06