

Product data sheet


RICHARD I (WALL FITTING)
9.841.2052.00
LEIPZIGER LEUCHTEN



IP
55

Mounting height approx. 3.00 - 4.50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stablized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge Wall luminaires Richard BI and BII as described above, except -Wall luminaire BI with opal cylinder, no mirror lamellae - Reflector made of impact-resistant RESIST plexiglas, inside finished in white paint, outside painted in colour Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp			
Nominal lamp power	100 W	LOR	59%
Lamp flux	10400 lm	ULOR	15%
Luminous efficacy	54 lm/W	Total flux	6153 lm
CCT	2000 K	Total power	115 W
CRI	25		

Mounting mode

Wall mounted

Electric

System power: 115 W

Shape and measurements

Height: 9.84 in
Diameter: 9.84 in

Protection

IP: 55