Product data sheet

ECLDISPLAYCASVW_BLACK
ECLDISPLAYCASVW_CW_WASH 2550DEG_MAX ZOOM
PROLIGHTS



IP 20 IK 08

EclDisplay is a range of revolutionary and flexible LED spotlights designed for galleries, retail and any public venue where an advanced but classical looking fixture is needed, with several control options, sources and optic versions available to precisely meet any application. The EclDisplay CAS VW is the version of the EclDisplay range made with integrated CASAMBI control on-board, leaving to System Integrators to install this luminaire in venues with their own wiring distribution and control. EclDisplay CAS VW includes a high-efficiency 35W Warm White + Cold White (Variable White - VW) LED capable of delivering a full tuneable White from 2700K to 5600K, and it is completed with a wide selection of optional profile (zoom and static) or wash lenses, and other optical accessories like louvres and snoots, making it a truly a multi-purpose fixture. Main features: CASAMBI control on-board 35W Variable White LED capable to deliver a full Tunable White from 2700K to 5600K Multiple lens options: profile (zoom and static) or wash optics

Light output 1



1 x LED

Nominal lamp power	32 W	LOR	100%
Lamp flux	1503 lm	Total flux	1506 lm
Luminous efficacy	47 lm/W	Total power	32 W
CCT	6055 K		
CRI	96		

Mounting mode

Ceiling mounted, Contact rail, Standing / Bollard

Shape and measurements

Length: 39.37 in
Width: 39.37 in
Height: 39.37 in

Adjustability

Rotatable, Tiltable, Free

Electric

System power: 32 W
Controller: DMX, DALI
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 65°C
Designation labels: CE