Product data sheet


HCC6 LED 6" CYLINDER DOWNLIGHT SERIES
HCC6S10D010MW-HM612830-61WDHWF
COOPER LIGHTING



IP 47

Lumens: 1,000, 1,500, 2,000, 3,000 and 4,000, 4 color temperatures: 2700K, 3000K, 3500K, 4000K CCT; CRI: 80 or 90, Distributions: Precision-formed reflectors in Narrow, Medium and Wide, Wall wash distribution with exclusive rotatable linear spread lens, Specular, Semi-Specular and White reflectors; Black or White baffles, Cylinder colors: Matte White, Matte Black, Bronze and Silver, Universal Voltage 120V – 277V; 0-10V analog dimming down to 1%, Mounting: wall, surface, pendant and aircraft cable, L70 at 50,000 hours (70% lumen maintenance at 50,000 hours)

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	80
Total flux	924 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	10 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in
Diameter: 6.00 in

Adjustability

Fixed

Electric

System power: 10 W

Protection

IP: 47