

# Product data sheet

ARCHITECTURAL LIGHTING  
V1-G1-72332-20N28-6602430 REGULA 2.0 1200MM SINGLE 24W 3000K LOW-VOLTAGE  
VARTON




IP  
66

IK  
07

Architectural linear wallwasher Flicker, %: 5 Length, mm: 1 164 Protection class: III Ingress protection (IP): IP66 Impact resistance: IK07 Power factor: 0,95 <https://www.varton.ru/products/arkhitekturnoe-osveshchenie/regula-2-0/regula-2-0-1200mm-odinochnye/svetodiodnyy-svetilnik-varton-arkhitekturnyy-regula-2-0-1200-mm-24-vt-3000-k-15x60-gradusov-dc24v-ra/>

## Light output 1



|                    |         |             |         |
|--------------------|---------|-------------|---------|
| 1 x LED            |         |             |         |
| Nominal lamp power | 24 W    | LOR         | 100%    |
| Lamp flux          | 2050 lm | Total flux  | 2050 lm |
| Luminous efficacy  | 85 lm/W | Total power | 24 W    |
| CCT                | 3000 K  |             |         |
| CRI                | 80      |             |         |

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 45.83 in  
Width: 1.89 in  
Height: 2.17 in

## Adjustability

Fixed

## Electric

System power: 24 W

## Protection

IP: 66  
IK: 07