



Product data sheet

ECLPENDANTSVW_WHITE
ECLPENDANTSVW_6000K_40DEG
PROLIGHTS



The EclPendant S merges elegant design with cutting-edge, eco-friendly technology, ensuring optimal illumination for any venue. This series of pendant lights offers a diverse range of LED sources, including options in RGB + Warm White, Variable White and single color (3000K, 4000K and 5600K), each featuring a 50 Watt LED that provides high-quality light output, uniform color, and remarkable durability. Completed by a wide range of optics, accessories, and versatile mounting solutions, the EclPendant S adapts to various installation needs. Mounting alternatives include pendant, surface, stem, wall, adjustable bracket, and recessed options. It can be directly wired to mains power (100-240 VAC or 48 VDC) and integrates seamlessly with control protocols like DMX + RDM and DALI, thanks to its accessible terminal blocks. User-friendly settings are manageable via the unit's onboard GUI, enhancing its functionality. The fixture's wide array of optics and accessories is designed for utmost flexibility and precision, allowing easy on-site changes without complications. Notably, the EclPendant S features a fan-free thermal design, ensuring quiet operation while delivering consistent and robust lumen output throughout its extended lifespan. * Please note: The hanging bracket is not included with the product. Main features: House light with 50W RGB + Warm White LED source with passive cooling 100-240 VAC or 48 VDC power input. Control via DALI, DMX, RDM Extensive mounting option, optics and accessories available

Light output 1



1 x LED			
Nominal lamp power	61.2 W	LOR	100%
Lamp flux	3562 lm	Total flux	3569 lm
Luminous efficacy	58 lm/W	Total power	61.2 W
CCT	6018 K		
CRI	96		

Mounting mode

Pendant, Ceiling mounted, Ceiling recessed

Shape and measurements

Length: 39.37 in
Width: 39.37 in
Height: 39.37 in

Adjustability

Rotatable, Free, Height adjustable

Electric

System power: 61.2 W
Controller: DMX, DALI
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 70°C
Designation labels: CE