Product data sheet

COMPACT LED EVO N 6300LM PLX 830 (60W) DALI
629457
LENA LIGHTING



IP 20 IK 07

629457 COMPACT LED EVO N 6300lm PLX 830 (60W) DALI Compact LED luminaire designed for surface mounting. Equipped with energy-saving LED modules and an evenly highlighted opal or prismatic diffuser, providing low glare (UGR<19)*. Made of plastic. Assembly or electrical connection does not require removing the diffuser. Available versions: - with DALI control, - with CORRIDOR function - the corridor function allows the illuminance in objects to be adjusted to changing conditions; in practice, it automatically reduces the luminous flux of the lamp from 100% to 10%.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	65 W	CRI	80
Total flux	6300 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	65 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.41 in
Width: 24.41 in
Height: 2.72 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: White

Electric

System power: 65 W
Ballast: ECG
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 07
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F