


Product data sheet

RELIANT LED HIGH BAY 33800 LUMENS, MEDIUM DISTRIBUTION, GLASS LENS
RRE-7MC2-JXXX-XXN
DIALIGHT



Reliant LED High Bay 33,800 Lumens 232 Watts 100-277V AC Cool White, 80CRI Glass Lens CE, ENEC EN 55015 IEC 61000-3-3 IEC 61547 IEC 61000-4-2 IEC 61000-4-3 IEC 61000-4-6 IEC 61000-4-8 IEC 61000-4-11 Medium Distribution IP66 LM79 Tested IES File

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	230.6 W	CRI	80
Total flux	35128 lm	LOR	100%
Luminous efficacy	152 lm/W	Total power	230.6 W

Mounting mode

Pendant

Shape and measurements

Height: 6.57 in
Diameter: 17.28 in
Weight: 9.3 kg

Adjustability

Rotatable, Tilttable

Electric

System power: 230.6 W
Voltage: 240 V AC, 120 V AC, 277 V AC, 110 V AC, 230 V AC
Appliance Class: I

Protection

IP: 66
IK: 05

Other operating numbers

Ambient temperature range: -40...149°F