


Product data sheet

TRACKLIGHT SPOT ZOOM DIM D85 25 W 3000 K 97R BK
4058075335806
LEDVANCE



Dimmable 3-phase tracklight spot with mechanical zoom lense. Product features: Mechanical zoom lens with a beam angle of 15 ° to 55 °. Dimmable (7% - 100%) via slider potentiometer directly on each luminaire. Excellent color rendering index CRI 97. Color rendering index $R_{a} > 90$. Initial color consistency: ≤ 4 SDCM. Rotation angle: 350°, tilt angle: 90°. Follows the unified LEDVANCE design language (SCALE design). Robust die-cast aluminum housing. Available in matt white (like RAL9016), matt black (like RAL9004). Luminaire efficacy: up to 70 lm/W. Product benefits: Dimmable 3-phase tracklight spot with mechanical zoom lense. Included 3-phase adapter compatible with common tracks (GLOBAL, EUTRAC, POWERGEAR, STAFF, NORLUX, NUCO, NORDIC). No distraction of attention from the illuminated objects thanks to reduced design. Low flicker light thanks to special electronic control gear. 5 years guarantee. Areas of application: Direct replacement for luminaires using HID lamps. Accent lighting. Galleries, museums. Fashion shops, accessories shops. Shops, changing rooms, shop windows. Hotels, restaurants, shops. Safety advice: All electrical connections must be made by a qualified person.. Caution, risk of electric shock..

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	25 W	CRI	97
Total flux	1500 lm	LOR	100%
Luminous efficacy	60 lm/W	Total power	25 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.66 in
Width: 3.35 in
Height: 10.43 in
Weight: 1.025 kg

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Black, White

Electric

System power: 25 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20
IK: 03
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -4...104°F