



Product data sheet

ALUMAX LED 1.4FT 4400/840
50460
TREVOS



chemically resistant, dustproof and waterproof industrial light fitting made of painted aluminium alloy; heat-strengthened safety glass with shatter pursuant to ČSN EN 12150-1; ON/OFF electronic driver (AC, DC on demand); Body: grey aluminium profile, powder coated; Diffuser: satin, heat-strengthened safety glass; Reflector: steel sheet, white (RAL 9003); Clips: stainless steel; Sealing: polyurethane (PUR) in the groove on the body; Connection: screwless three-pole terminal block; Power: 27,3 W; Luminaire flux: 3440 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK10; Ambient temperature: -25|45 °C; Weight: 4,2 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	27.3 W	CRI	80
Total flux	4520 lm	LOR	100%
Luminous efficacy	166 lm/W	ULOR	4%
		Total power	27.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 48.19 in
Width: 4.13 in
Height: 2.95 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: White
Designer: TREVOS

Electric

System power: 27.3 W
Ballast: ECG
Appliance Class: I

Protection

IP: 66
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...113°F