



Product data sheet

X-LINE SLIGHT SURFACE LED 5200 MICRO-PRM EDD 34 840 LINE-1S / L-2252MM
19.4308.4723.34
LUXIONA



Indoor luminaire. Assembly: directly mounted to ceiling construction. The body material is aluminum. Colour - RAL 9016 (white). Luminaire dimensions: 2252 x 34 x 68 mm. Diffuser: Micro-PRM (micro-prismatic diffuser PMMA). The efficiency of the optical system is 81,50%. Beam angle: (C0-C180) / (C90-C270) - 86,2° / 111°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 4919,3 lm. Power of luminaire: 31,4 W. Luminaire's light efficiency: 156,7 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED			
Nominal lamp power	31.4 W	LOR	83%
Lamp flux	6036 lm	Total flux	5038 lm
Luminous efficacy	192 lm/W	Total power	31.4 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 88.66 in

Width: 1.34 in

Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 31.4 W

Controller: DALI

Appliance Class: I

Protection

IP: 40

IK: 04

Other operating numbers

Ambient temperature range: 41...95°F