


Product data sheet

SMALL LINE SL S/D 63W 840 SENSOR WH-RAL9016
8726741598410
PERFORMANCE IN LIGHTING



LED free-standing luminaire for interior, including: Pole and light plate made of extruded aluminium profile, head piece made of die cast aluminium, sheet steel base, powder-coated / Slender plates with open spaces give the luminaire a uniquely delicate design / The fitting is available with different light optics: Gear tray with individual lenses of symmetrical distribution for optimum light diffusion / Gear tray with high-shine multifaceted reflectors made of pure aluminium for maximum luminaire efficiency and neutral colour rendering / Direct / indirect light distribution / Direct and indirect portions individually dimmable using TouchDIM (for version with sensor: direct and indirect portions dimmable in tandem using TouchDIM) / Colour rendering index Ra > 80 / Colour tolerance according to MacAdam = 3 SDCM / VDU application suitable acc. to EN 12464-1 / Sensor device available with task oriented PIRdetector and daylight control / Special colour versions available upon request

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 61 W | CRI | 80 |
| Total flux | 7941 lm | LOR | 100% |
| Luminous efficacy | 130 lm/W | ULOR | 5% |
| | | Total power | 61 W |

Mounting mode

Standing / Bollard

Shape and measurements

Length: 37.62 in
Width: 9.99 in
Height: 81.65 in

Design

Color of housing: White

Electric

System power: 61 W
Appliance Class: I

Protection

IP: 20