

Product data sheet


1W 3000K 30°
L371-L02
MP LIGHTING



IP
40

Application Interior directional in-grade luminaire for lighting walls, columns, architectural features or landscape features. Applicable for mounting into floors, walls, ceilings or other surfaces where a non-obtrusive luminaire is required. Suitable for walk-over and drive-over applications up to 5,500 Kg (12,000lbs). For wet and dry locations. IP Rating 40 Mounting Comes with aluminum flange. Designed to be cast into concrete or inserted into paving stone. Includes 6" wire lead. Electrical Powered by remote dimmable/ non-dimmable driver (sold separately). *See website for recommended drivers *Remote emergency driver / inverter options available. Consult factory. Power Consumption 1.5 Watt (at 350 mA, 1.0 Watt) 3.0 Watt (at 700 mA, 2.5 Watt) Light Output 1.0 Watt, 47~52lm 2.5 Watt, 75.2~79.4lm Warranty 5 years limited warranty Estimated useful life of LED is 50,000 hours. Material Solid anodized aluminum or marine grade stainless steel (316) with tempered glass lens, RoHS compliant.

Light output 1



1 x LED			
Nominal lamp power	1 W	LOR	86%
Lamp flux	52 lm	ULOR	86%
Luminous efficacy	45 lm/W	Total flux	45 lm
CCT	3000 K	Total power	1 W
CRI	80		

Mounting mode

Floor recessed

Electric

System power: 1 W

Shape and measurements

Length: 1.72 in
Width: 1.72 in
Height: 0.08 in

Protection

IP: 40

Adjustability

Fixed